

Appl. No. 10/829,338  
Amdt. dated April 01, 2005  
Reply to Office action of March 4, 2005

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

5 Claim 1-11 (cancelled)

Claim 12 (currently amended): A branched wire lock, ~~having a plurality of connection points,~~ comprising:

10 a trunk wire having ~~two ends fastening respectively to a coupling section for coupling respectively to an anchor object; and two coupling sections formed on its ends respectively, each of the coupling sections being capable of coupling with an anchor object; and~~

15 at least one branch wire ~~which has one end fastening to an annular ring to movably couple on the trunk wire and other end fastening to a lock head. has an annular ring to couple with the trunk wire and a lock head formed on its end.~~

Claim 13 (currently amended): The branched wire lock of claim 12, wherein one of the coupling sections is an annular ring.

20 Claim 14 (currently amended): The branched wire lock of claim 12, wherein one of the coupling sections is a lock head.

Claim 15-16 (cancelled)

25 Claim 17 (currently amended): The branched wire lock of claim 12, wherein the connection wire ~~consists of connection elements coupling with one another~~ comprises a plurality of branch wires that couple with the trunk wire.

Appl. No. 10/829,338  
Amdt. dated April 01, 2005  
Reply to Office action of March 4, 2005

Claim 18 (cancelled)

Claim 19 (original): The branched wire lock of claim 12, wherein the lock head is a jack lock.

5

Claim 20 (new) : A branched wire lock, comprising a connection wire comprises a trunk wire and at least a branch wire connecting to the trunk wire, wherein the trunk wire has a coupling section at one end of the trunk wire and a first lock head at the other end of the trunk wire, and the branch wire has a second lock head at one end.

10

Claim 21 (new): The branched wire lock of claim 20, wherein the connection wire is a flexible wire.

Claim 22 (new): The branched wire lock of claim 20, wherein the connection wire is a chain.

15

Claim 23 (new): The branched wire lock of claim 20, wherein the connection wire is a linkage bar.

20 Claim 25 (new): The branched wire lock of claim 20, wherein the coupling section is an annular ring.

Claim 26 (new): The branched wire lock of claim 20, wherein the coupling section is a lock head.

25

Claim 27 (new): The branched wire lock of claim 20, wherein the coupling section is a padlock.

Appl. No. 10/829,338  
Amdt. dated April 01, 2005  
Reply to Office action of March 4, 2005

Claim 28 (new): The branched wire lock of claim 20, wherein the first lock head and the second lock head are jack locks.

5 Claim 29 (new): The branched wire lock of claim 28, wherein the jack locks are able to latch on electronic devices and computers.

Claim 30 (new): The branched wire lock of claim 20, wherein the connection wire comprises a plurality of branch wires.

10 Claim 31 (new): The branched wire lock of claim 30, wherein the connection wires are connected to the truck wire at a same radial location.

15 Claim 32 (new): The branched wire lock of claim 30, wherein the branch wires are fastened to a distal end of the truck wire.

Claim 33 (new): The branched wire lock of claim 30, wherein the branch wires connect to a sub-substrate wire which has a lock head at one end.

20 Claim 34 (new): The branched wire lock of claim 30, wherein each of the branch wires further comprises an annular ring to be employed in coupling on the trunk wire.

Claim 35 (new): The branched wire lock of claim 34, wherein each of the annular rings is a string knob or a coupling ring.

25 Claim 36 (new): The branched wire lock of claim 34, wherein each of the annular rings is able to adjust the responding branch wire location.